

ECO LED Batten Gen4

The Pierlite Eco LED Batten Gen4 is a one box solution with Colour and Lumen select feature. The quick release clips, removable connector and sealed LED module makes it easy to install and maintain. With up to 110lm/W, the efficacy makes it an ideal replacement for traditional flourescent battens.

- Comes with an opalised diffuser for even light distribution
- Uses quick release clips and removable connectors for easy installation.
- Increased visual comfort with less than 1% flicker.



LUMEN^{SELECT} COLOUR^{SELECT}



80

CRI



IP20

Ingress
Protection
Rating



5SDCM

MacAdam
Steps



0 to 40

Operating
Temperature



Non -
Dimmable

Dimming



5 Years

Warranty



Symmetric


Beam
Distribution




120°

Beam Angle


CODE	SYSTEM POWER	EXIT LUMEN	EFFICACY	CCT	DIMENSIONS	WEIGHT	INRUSH CURRENT	SENSOR TYPE
ECOBAT202ECSLSG 4	18W	2000lm	110lm/W	4000K	L603 x W74 x H74 mm	0.80kg	14A	
	14W	1500lm		5000K				
	16W	1700lm		6500K				
	11W	1200lm						
ECOBAT202ECSSLSS G4	18W	2000lm	110lm/W	4000K	L603 x W74 x H74 mm	0.80kg	14A	Microwave
	11W	1200lm						
	14W	1500lm		5000K				
	16W	1700lm		6500K				
ECOBAT404ECSLSG 4	36W	4000lm	110lm/W	4000K	L1164 x W74 x H74 mm	1.5kg	17A	
	20W	2300lm						
	25W	3000lm		5000K				
	30W	3500lm		6500K				
ECOBAT404ECSSLSS G4	36W	4000lm	100lm/W	4000K	L1164 x W74 x H74 mm	1.5kg	17A	Microwave
	20W	2300lm						
	25W	3000lm		5000K				
	30W	3500lm		6500K				
ECOBAT505ECSLSG 4	50W	6900lm	110lm/W	4000K	L1500 x W74 x H74 mm	1.8kg	25A	
	30W	4200lm						
	35W	5000lm		5000K				
	45W	6000lm		6500K				
ECOBAT505ECSSLSS G4	50W	6900lm	110lm/W	4000K	L1500 x W74 x H74 mm	1.8kg	25A	Microwave
	30W	4200lm						
	35W	5000lm		5000K				
	45W	6000lm		6500K				



ECOBAT202ECSLSG4, ECOBAT202ECSLSSG4



ECOBAT404ECSLSG4, ECOBAT404ECSLSSG4



ECOBAT505ECSLSG4, ECOBAT505ECSLSSG4

Product Images

