

MaxiMaster Floodlight Gen3

MML250LSCSS

- Provided with multiple wattages/lumen outputs in 1 fitting with wattages of 100W/150W/200W/250W and colour select with 3000K/4000K/5000K with symmetrical distribution
- Supplied with 2x 20mm cable entries, 2 x 20mm metal cable gland, 6mm² terminal block and an additional 10KV surge protection installed to the 4KV driver surge immunity
- Chromated pressure die-cast LM6 marine grade aluminium body with black powder coated paint finish



LUMEN SELECT[™] COLOUR SELECT

Performance

System Power	250W, 250W, 200W, 150W, 100W, 200W, 150W, 100W, 250W, 200W, 150W, 100W
Exit Lumen	36200lm, 33600lm, 27500lm, 21800lm, 15000lm, 29300lm, 23100lm, 15500lm, 34800lm, 28500lm, 22800lm, 15600lm
Efficacy	158lm/W, 139lm/W, 146lm/W, 152lm/W, 159lm/W, 162lm/W, 152lm/W, 169lm/W, 145lm/W, 153lm/W, 159lm/W, 165lm/W
CCT	4000K, 3000K, 5000K
CRI	80
Operating Temperature	0 to 50
Ingress Protection Rating	IP66
Impact Rating	IK08
Beam Distribution	Symmetric
Warranty	5 Years
Lifetime	54,000hrs (L70/B50) @ 50°C


Physical

Dimensions	L523 x W342 x H185 mm
Diffuser	Glass
Luminaire Colour	Black
Weight	6.2kg
Luminaire Material	Aluminium (Die Cast)
Driver Location	Integrated
Finish	Powder Coated
Installation	Trunnion

Electrical

Dimming	Non - Dimmable
Voltage	240V
Inrush Current	65A
Inrush Current Duration	240µs
Line Current	1.1A
Surge protection	Yes
Electrical Rating	Class 1

Line Drawings



Product Images



