

CONSTRUCTION - PVC CABLES 0.6/1 kV

2C+E PVC CIRCULAR SWA

PVC INSULATED LAID UP PVC BEDDED GSW ARMoured AND PVC SHEATHED CABLE TO AS/NZS 5000.1.

For mains, submains and subcircuits unenclosed, in conduit, buried direct or in underground ducts for buildings and industrial plants where mechanical damage may occur.




Cable Characteristics



Semi-rigid



12D



2


Water
Splashes


Good


+75 °C
-15 °C


C3



Good

Cable Design

CONDUCTOR:

Plain annealed copper conductor to AS/NZS 1125
Maximum continuous operating temperature: 75 °C

Can also be operated at temperatures up to 90 °C when not exposed to mechanical deformation (see AS/NZS 3008.1)

INSULATION:

V-90 PVC
Colours: Red, Black, Green/Yellow


ARMOUR:

Steel wire armour


SHEATH:

5V-90 PVC
Colours: Orange


Installation Conditions


INDUSTRIAL
EQUIPMENT



18D




IN FREE AIR




IN GROUND




MACHINES



0 °C



IN TRENCH



IN DUCT


EXTERNAL
BUILDING

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group; any modification or alteration afterwards of product may give different result. The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.



CONSTRUCTION - PVC CABLES 0.6/1 kV - 2C+E PVC CIRCULAR SWA**Physical & Electrical Characteristics**

Product code	Conductor			Cable				Min. installed bending radius mm
	Nominal C.S.A. mm ²	Number and diameter of wires No/mm	Nominal diameter mm	Nominal insulation thickness mm	Overall diameter		Approx. mass kg/100 m	
					Minimum mm	Maximum mm		
1.52CEOCA	1.5	7/0.50	1.5	0.8	14.5	15.6	48	190
2.52CEOCA	2.5	7/0.67	2.0	0.8	15.8	16.8	57	200
42CEOCA	4	7/0.85	2.6	1.0	17.2	18.3	68	220
62CEOCA	6	7/1.04	3.1	1.0	18.2	19.4	78	235
102CEOCA	10	7/1.35	4.1	1.0	20.6	22.0	96	265
162CEOCA	16	7/1.70	5.1	1.0	22.7	24.0	119	290
252CEOCA	25	19/1.35	6.8	1.2	26.5	27.8	166	340

Conductor nominal C.S.A. mm ²	Current rating (a)			Electrical characteristics	
	Unenclosed spaced A	Buried direct A	Underground in duct A	Maximum D.C. resistance at 20°C Ω/km	Reactance per core Ω/km
1.5	19	28	22	13.6	0.111
2.5	27	40	31	7.41	0.102
4	37	52	40	4.61	0.102
6	46	65	51	3.08	0.0967
10	64	87	68	1.83	0.0906
16	85	115	88	1.15	0.0861
25	115	145	115	0.727	0.0853

(a) Based on 75 °C conductor temperature, 40 °C ambient air temperature and where applicable, burial depth of 0.5 m, soil temperature of 25 °C and soil thermal resistivity of 1.2 °C.m/W. Refer to AS/NZS 3008.1 for other installation conditions.

Conductor nominal C.S.A. mm ²	Diameter under armour		Diameter over armour		Armour wire diameter mm
	Minimum mm	Maximum mm	Minimum mm	Maximum mm	
1.5	8.4	9.1	10.9	11.6	1.25
2.5	9.7	10.3	12.2	12.8	1.25
4	11.1	11.8	13.6	14.3	1.25
6	12.1	13.0	14.6	15.5	1.25
10	14.5	15.5	17.0	18.0	1.25
16	16.6	17.6	19.1	20.1	1.25
25	19.7	20.7	22.9	23.9	1.60

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group; any modification or alteration afterwards of product may give different result. The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.



CABLE HANDLING

Cable Usage Characteristics

**AMBIENT TEMPERATURE**

Maximum operating temperature
Minimum operating temperature

**MECHANICAL IMPACT RESISTANCE**

1	Light Impact
2	Moderate Impact
3	Heavy Impact
4	Very Heavy Impact

**RESISTANCE TO SOLAR RADIATION AND WEATHER**

Excellent	Permanent
Very Good	Frequent
Good	Occasional
Acceptable	Accidental
Poor	None

**BEHAVIOUR IN FLAME AND FIRE**

Reaction To Fire	Resistant To Fire
C 1 Fire retardant	Level 1 Ultimate fire survival
C 2 Flame retardant	Level 2 Two hours fire survival
C 3 No fire performance	Level 3 Restrained spread & self extinguishing

**HALOGEN FREE**

AS/NZS 4507

**MINIMUM BENDING RADIUS**

Minimum bending radius of installed cables

**CHEMICAL RESISTANCE**

Excellent	Permanent
Very Good	Frequent
Good	Occasional
Acceptable	Accidental
Poor	None

**RESISTANCE TO WATER**

Negligible	No humidity
Water Drops	Occasional condensation
Spray	Water run off
Splashes	Exposed to water splashes
Heavy Sea	Exposed to waves
Immersion	Temporarily covered by water
Submersion	Permanently covered by water

**FLEXIBILITY**

Rigid	Flexible
Semi-rigid	Very flexible


**LOW SMOKE EMISSION**

AS/NZS 4507


Laying Conditions




MINIMUM BENDING RADIUS
DURING INSTALLATION



IN TRENCH




IN GROUND



IN DUCT




DOMESTIC
APPLIANCES




MACHINES




MOBILE
EQUIPMENT




SUBMERGED




OVERHEAD AERIAL




MIN. INSTALLATION
TEMPERATURE



IN FREE AIR



IN GROUND WITH
PROTECTION



IN CONDUIT



OUTDOOR
APPLIANCES



FESTOON



INTERNAL
WIRING



INDUSTRIAL
EQUIPMENT



EXTERNAL
BUILDING

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group; any modification or alteration afterwards of product may give different result. The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.

