


M@X6®

Unshielded Twisted Pair (UTP) Category 6

Cable Design

EIA/TIA 568-C.2
AS/NZS 3080
ACMA - AS/CA S008



- Drawing not to scale -

- **Multi-pair construction**
- **Conductor:** Annealed solid copper wire 0.51mm diameter (24 AWG)
- **Insulation:** Polyethylene compound in compliance with AS1049
- **Cabling element:** Twisted pair
- **Colour code:** See table 1
- **Stranding of pairs:** Bunched around cross web filler
- **Sheath:** Flame retardant PVC (75°C) in compliance with AS 1049

100Ω balanced UTP cable suitable for Local Area Network (LAN) cabling up to 250 MHz capable of supporting transmission rates of up to and including 10-Gigabit Ethernet. Cable is UL verified (see *Note 1*).

Technical data

Number of Pairs		4
Cable nominal diameter	mm	6.0
Cable nominal weight	kg/km	40
Max. pulling tension	N	190
Min. bending radius	mm	50
Temperature range	°C	Installation 0 -> +50 Operation -20 -> +60

Note 1: Cable meets IEC 60332-1 "Test for vertical flame propagation for a single insulated wire or cable"

Identification

Sheath Colour:

The standard outer sheath colour is grey (RAL 7044). Alternative colour is blue (RAL 5019).

Sheath Marking:

The outer sheath is marked in 1 meter intervals as follows:

PRYSMIAN M@X6 4PR CATEGORY 6 VERIFIED (UL) E179849G UTP 24AWG TYPE CMX XXXX MM/YY T/N ##### ***M**

Where: XXXX = L4P6 for cables with grey sheath, L4P6BU for blue sheath

Transmission characteristics

Frequency [MHz]	Return Loss [dB] Min	Attenuation [dB/100m] Max	NEXT [dB] Min	PS NEXT [dB] Min	ACRF [dB/100m] Min	PS ACRF [dB/100m] Min	Propagation Delay [ns/100m] Max	Propagation Delay Skew [ns/100m] Max
1.0	20+5log(f)	2.0	74.3	72.3	67.8	64.8	570	45
4.0		3.8	65.3	63.3	55.8	52.8	552	
8.0		5.3	60.8	58.8	49.7	46.7	547	
10.0	25	6.0	59.3	57.3	47.8	44.8	545	
16.0		7.6	56.2	54.2	43.7	40.7	543	
20.0	25-7log(f/20)	8.5	54.8	52.8	41.8	38.8	542	
25.0		9.5	53.3	51.3	39.8	36.8	541	
31.25		10.7	51.9	49.9	37.9	34.9	540	
62.5		15.4	47.4	45.4	31.9	28.9	539	
100		19.8	44.3	42.3	27.8	24.8	538	
200		29.0	39.8	37.8	21.8	18.8	537	
250		32.8	38.3	36.3	19.8	16.8	536	

Electrical characteristics

DC resistance [Ω /100m]:	9.38 Max.
Resistance unbalance [%]:	5 Max.
Mutual capacitance @1kHz [pF/100m]:	5.6 Max.
Capacitance unbalance @1kHz, pair to ground [pF/100m]:	330 Max.

Note: All electrical characteristics are given at 20°C

Table 1. Colour code / Pair identification

Pair number	Insulation colour				
	Wire a	Wire b		Wire a	Wire b
1	Blue	White blue stripes (2)	3	Green	White green stripes (2)
2	Orange	White orange stripes (2)	4	Brown	White brown stripes (2)

Logistic
Packing:

Fibreboard 'easy-pull' dispenser cartons (Reelex) – 335 x 350 x 370 mm (Red / White)

Delivery Lengths:

Standard delivery length is 305 metres

© PrysmianGroup 2012, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by PrysmianGroup: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of PrysmianGroup. The information is believed to be correct at the time of issue. PrysmianGroup reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by PrysmianGroup.