LIGHTING CONTROLS

EXTERNAL PIRS







PROTON multi-directional 180° PIR, IP54


- Suitable for outdoor applications
- Manual over ride with automatic reset after 8 hours
- Passive infra red ensures light is switched on when sensor detects movement of heat, switched off when area is vacated. Minimises false / unwanted triggering
- Large terminals accept 2 x 1.5mm² conductors in each terminal. Facility for loop in loop out
- Earth terminal included

- 3 wire multiple sensors can be wired in parallel
- High load contact rating, allows numerous fittings to be switched
- No minimum load requirements
- Complete with accessory shield to reduce detection angle
- Corner mounting bracket available as accessory code: RPRBRK-01

White	RPR180PIR-01
Black	RPR180PIR-04
Detection Area:	180°
Motion Detection Range:	12m diameter at 2.5m
Loading:	Max 300W fluorescent
	Max 300W LED
	Max 1,200W incandescent
Time Settings:	10 seconds to 15 minutes adjustable
Lux Cottings.	2 20001

	Max 1,200W incandescent
Time Settings:	10 seconds to 15 minutes adjustable
Lux Settings:	3-2000lx
IP:	54
Depth (mm):	118
Width (mm):	80
Height (mm):	51
Box Qty:	1
Weight (kg):	0.16







Accessories:

RPRBRK-01 C RPRBRK-04 C

Corner mount accessory, white Corner mount accessory, black