

CANOPY SHP205

IP66 LED recessed or surface mount canopy luminaire

Application

Commerical or industrial canopy applications

Design Specifications

- Stylish die-cast aluminium body
- Durable white powder coated finish
- High efficiency SMD LED chips, Clear tempered glass diffuser, 120 degree beam
- Built-in constant current non-dimmable LED driver
- Suits most traditional Canopy size (SHP205 RC)
- Symmetrical light distribution, 300 mm 3 core rubber flex




Technical Specification

Model No.	Description	Input (V)	Power (W)	Lumens (lm)	CCT (K)	Beam Angle (°)
SHP205/110RC	LED CANOPY 110W LRG REC. 5K WH *	240	110	14300	5000	120
SHP205/110RCS	LED CANOPY 110W SML REC. 5K WH *	240	110	14300	5000	120
SHP205/110SM	LED CANOPY 110W SURFACE 5K WH *	240	110	14300	5000	120
SHP205/150RC	LED CANOPY 150W LRG REC. 5K WH	240	150	14300	5000	120
SHP205/150RCS	LED CANOPY 150W SML REC. 5K WH 1/CTN 36/ PLT	240	150	19500	5000	120
SHP205/150SM	LED CANOPY 150W SURFACE 5K WH	240	150	19500	5000	120
SHP205/75RC	LED CANOPY 75W LRG REC. 5K WH *	240	75	9750	5000	120
SHP205/75RCS	LED CANOPY 75W SML REC. 5K WH *	240	75	9750	5000	120
SHP205/75SM	LED CANOPY 75W SURFACE 5K WH *	240	75	9750	5000	120


Model No.	CRI	Body Colour
SHP205/110RC	75	WHITE
SHP205/110RCS	75	WHITE
SHP205/110SM	75	WHITE
SHP205/150RC	75	WHITE
SHP205/150RCS	75	WHITE
SHP205/150SM	75	WHITE
SHP205/75RC	75	WHITE
SHP205/75RCS	75	WHITE
SHP205/75SM	75	WHITE

Dimensions


SHP205 RC



SHP205 RCS




SHP205 SM




Photometric Data


SHP205 - 75



SHP205 - 150



SHP 205 - 110



Product Images

