



## GU10L TC - 4/6W

High efficiency GU10L TC LED lamps

### Application

Energy efficient LED lamp solutions, ideal for residential luminaires

### Design Specifications

- Frosted polycarbonate lens
- Poly covered aluminium body
- High efficiency SMD LED chip, CRI >80
- Integral LED driver, non-dimmable, 240V
- Colour temperature selectable 3000K / 4000K / 6000K
- Beam distribution 50° , GU10 lamp base, double insulated



### Technical Specification

Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	CRI	Beam Angle (°)
GU10L350TC	240	4	360/400/380	3000/4000/6000	80	50
GU10L550TC	240	6	500/600/550	3000/4000/6000	80	50


Model No.	Dimmable	Base Type
GU10L350TC	NO	GU10
GU10L550TC	NO	GU10

**IMPORTANT**, where CCT selection switching is provided, it is important to switch OFF the SUPPLY before the CCT selection is made, otherwise equipment damage may occur.

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

## Dimensions

### Dimensions



# THE SFI SYSTEM ELIMINATES LED FLICKERING.

SIMPLY  
**MATCH** THE  
UNIFIT SFI  
DOWNLIGHT  
WITH THIS  
**SDD400SFI**  
DIMMER.



**DIM with  
FLICKER  
CONTROL**

For related  
products  
please  
scan me

