



LED STD25 NT

Wide body LED surface mount diffused linear batten

Application

Conventional linear LED batten profile ideal for residential and commercial spaces

Design Specifications

- Durable metal body profile, white powder coat finish in two traditional sizes, twin and single lamp configuration
- Optional (to order separately) choice of 3000,4000,6000K, CRI>80 LED tubes
- Large terminal block, easy installation
- Safety fuse installed
- High performance PMMA prism diffuser, beam distribution 120 degree
- Dimensions: (L x W x H mm) STD25/106 - 620 X 83 X 69mm, STD25/206 - 620 X 83 X 109mm, STD25/112 - 1230 X 83 X 69mm, STD212/NT - 1230 X 83 X 109mm.



Technical Specification

Model No.	Description	Input (V)	Body Colour
STD25/106NT	LED DIFFUSED BATTEN 1 X 18W PROFILE NO TUBE	240	WHITE
STD25/206NT	LED DIFFUSED BATTEN 2 X 18W PROFILE NO TUBE	240	WHITE
STD25/112NT	LED DIFFUSED BATTEN 1 X 36W PROFILE NO TUBE	240	WHITE
STD25/212NT	LED DIFFUSED BATTEN 2 X 36W PROFILE NO TUBE	240	WHITE