



NEON BEND FLN2407

FLEXIBLE NEON STRIP, 24V DC low voltage, IP66

Application

A very flexible solution for residential and commercial interior spaces

Design Specifications

- High efficiency SMD LED chips, luminous efficacy up to 85lm/w, beam distribution 180 degree.
- Roll length 10m, cuttable every 50mm at scissors symbol ✂
- EPR standard compliant, with smooth colour uniformity
- Blue, Green, Yellow, Red or White in 3000, 4000, 6500K colour choices, CRI >80
- Driver ordered separately, power 7.2W/m
- Lumen performance, Blue 50lm/m, Green 180lm/m, Red 45lm/m, Yellow 45lm/m, 3000K 290lm/m, 3000K 290lm/m, 4000K 290lm/m, 6500K 300lm/m



Performance

Dimmable Driver - **OPTIONAL**

Dimmer Type - **LED controller**


Technical Specification

Model No.	Description	Input (V)	Power (W)	Lumens (lm)	CCT (K)	CRI
FLN2407WW17	NEON BEND 24V DC 7W 3K	24V DC	7	500	3000	80
FLN2407CW17	NEON BEND 24V DC 7W 4K	24V DC	7	520	4000	80
FLN2407DL17	NEON BEND 24V DC 7W 6.5K	24V DC	7	500	6500	80
FLN2407YW17	NEON BEND 24V DC 7W YELLOW	24V DC	7	45		80
FLN2407RD17	NEON BEND 24V DC 7W RED	24V DC	7	45		80
FLN2407GN17	NEON BEND 24V DC 7W GREEN	24V DC	7	180		80
FLN2407BU17	NEON BEND 24V DC 7W BLUE	24V DC	7	50		80

Model No.	Dimmable Driver
FLN2407WW17	OPTIONAL
FLN2407CW17	OPTIONAL
FLN2407DL17	OPTIONAL
FLN2407YW17	OPTIONAL
FLN2407RD17	OPTIONAL
FLN2407GN17	OPTIONAL
FLN2407BU17	OPTIONAL

Dimensions

WIRING DIAGRAM



Product Images

