



PLUTO DIM 1150 QP

Australian approved 1-10V dimmable constant current LED driver with selectable output

Application

The perfect choice for constant current electronic lighting circuits

Design Specifications

- SELV and EMC compliant, safe no load operation
- Compact design profile, electrical class II
- Overload and short circuit protection
- Dimmable 1-10V, dimming range 10%~100%
- Secondary output range 1150/1000/850/700mA
- Auxiliary 12V DC power source (maximum sink current 40mA)



Performance

Dimmable - **YES**

Dimmer Type - **1-10V**

Technical Specification

Model No.	Input Voltage (V/AC)	Frequency (Hz)	Power (W)	Output Current (mA)	Power Factor	Dim (mm)
PLUTO 1150/60QP/A	240	50	60	1150	0.9	180(L) x 46(W) x 30(H)

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

THE SFI SYSTEM ELIMINATES LED FLICKERING.

**DIMMABLE
CONTROL WITH
SFI FLICKER
CONTROL
TECHNOLOGY**
when paired with
SAL SFI downlights



**DIM with
FLICKER
CONTROL**

For related
products
please
scan me

