



Main

Range of product	Acti 9
Device short name	IHH 7j 1c ARM
Product or component type	Mechanical time switch
Number of channels	1
Function available	Manual time changeover

Complementary

Device application	Building
Load type	7 fluocompact lamp, (7 W) 7 fluocompact lamp, (20 W) 7 fluocompact lamp, (15 W) 7 fluocompact lamp, (11 W) 3 parallel-corrected fluorescent tube, (100 W) 230 V AC incandescent lamp, (1000 W) 230 V AC halogen lamp, (1000 W) 15 parallel-corrected fluorescent tube, (40 W) 10 parallel-corrected fluorescent tube, (58 W)
Cycle duration	7 days
Measurement accuracy	+/- 1 s/day
Maximum number of switchings	42 on - 42 off
Minimum interval duration	2 h
Type of setting	Manual time changeover
Measurement accuracy	+/- 1 s/day 20 °C
Power consumption	2.5 VA
Maximum switching current	4 A - 250 V AC pf = 0.6 16 A - 250 V AC pf = 1
[Ue] rated operational voltage	(+/- 10 %) 230 V AC 50/60 Hz
Battery life	10 yr
Backup time	100 h time and program saving
Mounting support	DIN rail
9 mm pitches	2
Colour tint	White(RAL 9003)
Connections - terminals	Screw terminals
IP degree of protection	IP20 B
Width	18 mm
Height	90 mm
Depth	66 mm
Product weight	0.101 kg

Environment

Ambient air temperature for operation	-10...50 °C
IP degree of protection	Terminals : IP20 B

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0626 - Schneider Electric declaration of conformity
REACH	Reference contains SVHC above the threshold - go to CaP for more details
Product environmental profile	Available
Product end of life instructions	Available Download End Of Life Manual