



Main

Commercial Status	Commercialised
Relay application	Remote control
Range of product	ITL
Device short name	IETL iTL 32
Poles description	1P
Pole contact composition	1 NO
[In] rated current	32 A
Network type	AC

Complementary

Network frequency	50/60 Hz
[Ue] rated operational voltage	415 V AC 50/60 Hz
Control type	Remote control Toggle
Control signal type	Impulse
Switching frequency	5 switching operations/minute
Impulse duration	50 ms
Remote control type	Illuminated pushbutton 3 mA
Local signalling	ON/OFF indication
Control circuit voltage	230/240 V AC 50/60 Hz 110 V DC
Supply inrush power	19 VA
Mounting mode	Fixed, on right side of TL
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	2
Height	60 mm
Width	18 mm
Depth	84 mm
Colour	White
Electrical durability	AC-22: 20000 cycles AC-21: 50000 cycles
Connections - terminals	Tunnel type terminals <= 10 mm ²
Product compatibility	ITL 32A

Environment

Standards	EN 669-1 EN 669-2-2
Noise level	<= 60 dB
Tropicalisation	2
Relative humidity	95 % (55 °C)
Ambient air temperature for operation	-20...50 °C

RoHS compliance

RoHS EUR status	Compliant
RoHS EUR conformity date(YYWW)	0910

Contractual warranty

Period	18 months
--------	-----------