Product data sheet Characteristics

EY56P420

Easy56 Plug - 4 Pin - 20A - 500V



Main

| Product name | Easy56 |
|---------------------------|------------------------|
| Product or component type | Plug |
| Device short name | EY56P420 |
| Plug, socket category | Low voltage |
| Poles description | 3P + E |
| Pin number | 4 pins |
| Shape of pin | Tubular |
| Outlet standard | Australian/New Zealand |

Complementary

| Plug, socket, control station shape | Straight |
|-------------------------------------|----------------------------------------|
| [In] rated current | 20 A |
| [Ue] rated operational voltage | 500 V |
| Network type | AC |
| Network frequency | 50 Hz |
| Contacts material | Brass pins : |
| Connections - terminals | Screw terminals |
| Cable cross section | 14 mm² |
| Cable outer diameter | 716 mm |
| Wire stripping length | 1035 mm |
| Cable entry | Cable gland |
| Product weight | 0.298 kg |
| Height | 78 mm |
| Width | 78 mm |
| Depth | 152 mm |
| Colour | Clear body Orange (RAL 2004) plug |
| Targeted country | Australia New Zealand |
| Market segment | Utility Small commercial Industry |

Environment

| Standards | AS/NZS 3123 | |
|---------------------------------------|-----------------------------|--|
| IP degree of protection | IP66 conforming to AS 60529 | |
| Ambient air temperature for operation | -2575 °C | |
| Ambient air temperature for storage | -2575 °C | |

Offer Sustainability

| - · · · · · · · · · · · · · · · · · · · | |
|-----------------------------------------|---------------------------|
| Sustainable offer status | Not Green Premium product |