

Refer catalogue SACS

Accessories ¹⁾



CZ pneumatic timer


Function/Description		Cat. No.	
Pneumatic timer		On-delay 0.3-30 s	CZE 7-30
		On-delay 1.8-180 s	CZE 7-180
Pneumatic timer		Off-delay 0.3-30 s	CZA 7-30
		Off-delay 1.8-180 s	CZA 7-180

Electronic timer on-delay for in line connection. (clips onto CA 7 coil).

Operating voltage 110...240 V 50/60 Hz, 110...250 V DC.



CRZE 7 timer on-delay




Time range 0.1...3 s	CRZE 7-3
Time range 1...30 s	CRZE 7-30
Time range 10...180 s	CRZE 7-180

Electronic timer off-delay for in line connection. (clips onto CA 7 coil).

Operating voltage 110...240 V 50/60 Hz.



CRZA 7 timer




Time range 0.1...3 s	CRZA 7-3
Time range 1...30 s	CRZA 7-30
Time range 10...180 s	CRZA 7-180

Electronic timer for star delta starting. In line connection clips on main contactor.

Operating voltage 110...240 V 50/60 Hz, 110...250 V DC. Changeover transition 90 mS.



CRZY 7-30 timer



Time range 0.1...30 s	CRZY 7-30
-----------------------	------------------

Mechanical interlock for all CA 7 contactors which can also be used between CA 7 of different ratings.

Standard version or version with integrated N/C contacts for electrical interlocking.

Adds 9 mm to width and includes connecting dovetail.



CM 7-02 mechanical interlock with 2 x N/C contacts

	Interlock only	CM 7
	Interlock with 2 x N/C contacts	CM 7-02

Note: ¹⁾ Accessories are suitable for all CA 7 contactors.