

Catalogue No: **M-SDS7-15-240VAC**

STARTER STAR DELTA 15kW 240V AC CONTROL

Motor Control and Drives > Motor Starting and Protection > Assembled Motor Starters > Sprecher + Schuh Motor Starters > Star Delta Motor Starters > M-SDS7 Streamline Star Delta Motor Starters 7.5 to 75kW



Star Delta Starter 15KW, With 5.4...27A Electronic Overload, IP66 Steel Enclosure, Control Voltage 240V AC, Stop/Start And Reset Pushbuttons, Adjustable Changeover Time (1.5...30 Seconds)

- Wide range of NHP motor starting method versions available, allowing for correct selection of a motor starter to suit the application load condition requirements during starting
- Available in a number of IP ratings and enclosure type, to allow selection to meet the different installation environments

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

kW Rating, AC-3, 415V	15 kW @415V
Component Type Motor Control and Drives	Star-Delta Starter
Motor FLC, Min	5.4 A, min
Motor FLC, Max	27 A, max
IP Rating	IP66
Motor Connection	3 wire
Enclosure Type	Steel enclosed (IP 66)
Control Voltage, AC, Nom	240 V AC
Button Arrangement	Start / Stop Reset

REFERENCES

IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-

Catalogue No: **M-SDS7-15-240VAC**

STARTER STAR DELTA 15kW 240V AC CONTROL

Motor Control and Drives > Motor Starting and Protection > Assembled Motor Starters > Sprecher + Schuh Motor Starters > Star Delta Motor Starters > M-SDS7 Streamline Star Delta Motor Starters 7.5 to 75kW



Technical Diagram