


Product Line: Stanilite®
Product Group: Excel LED Spitfire® Range
Additional Description: 2 x Twin LED Spitfire Batten



Catalogue No.	Description
SFBAT2X2LED	Spitfire 2 x Twin LED Batten Non-maintained
SFBAT2X2LEDM	Spitfire 2 x Twin LED Batten Maintained
SFBATNXS2X2LED	Spitfire Nexus LX 2 x Twin LED Batten Non-maintained
SFBATNXS2X2LEDM	Spitfire Nexus LX 2 x Twin LED Batten Maintained
SFBATNRF2X2LED	Spitfire Nexus RF 2 x Twin LED Batten Non-maintained
SFBATNRF2X2LEDM	Spitfire Nexus RF 2 x Twin LED Batten Maintained

Features:

- LED technology 50,000 hours lamp life
- High emergency classification and low maintenance cost - ideal for warehouse, supermarket, factory, carpark and open areas
- High temperature NiCad batteries
- Large terminal block (16mm²) for easy wiring
- Available in Standard, Nexus® LX monitored or Nexus RF monitored
- Wall or ceiling mounted
- Maintained versions can be utilised for after hours and security lighting and can also be used to provide lighting during general lighting turn to delay or restrike
- Protective wire guard available

Dimensions:

Length	Width	Height
1220mm	118mm	43mm

Weight:

Model	Weight
Non-maintained	3.9kg
Maintained	4.1kg

Construction:

Part	Construction
Body	White Powder Coated Steel
Wire Guard	White Powder Coated Galv Steel

Light Source:

Model	Light Source
All Models	Two 3W Twin LED Lamps

Power Consumption:

Model	Power Consumption
Standard	8.0W
Nexus LX	8.5W
Nexus RF	8.5W

Photometrics:

Model	Class	Classification
All Models	C0 C90	D100 D100

NB: Bare and Wire Guard

Spare Parts:

Catalogue No.	Description
03-01017P	Battery 5 Cell D NiCad Side by Side 6.0V 4.0Ah

Accessories:

Catalogue No.	Description
WG236	Wire Guard to suit 2 x Twin LED Spitfire Batten

Thomas & Betts emergency lighting products are designed to comply with AS2293 and meet relevant Australian EMC Standards.
Due to ongoing product development, specification changes may result.