

M205 GLASS FUSES


Bel Fuse / Bussmann

ELECTRONIC

Fast Acting (F) Part Number	Time Delay (T) Part Number	Ampere Rating
SWE-M205.032	SWE-M205DA.032	32mA
SWE-M205.040	SWE-M205DA.040	40mA
SWE-M205.050	SWE-M205DA.050	50mA
SWE-M205.063	SWE-M205DA.063	63mA
SWE-M205.080	SWE-M205DA.080	80mA
SWE-M205.100	SWE-M205DA.100	100mA
SWE-M205.125	SWE-M205DA.125	125mA
SWE-M205.160	SWE-M205DA.160	160mA
SWE-M205.200	SWE-M205DA.200	200mA
SWE-M205.250	SWE-M205DA.250	250mA
SWE-M205.315	SWE-M205DA.315	315mA
SWE-M205.400	SWE-M205DA.400	400mA
SWE-M205.500	SWE-M205DA.500	500mA
SWE-M205.630	SWE-M205DA.630	630mA
SWE-M205.800	SWE-M205DA.800	800mA
SWE-M205001	SWE-M205DA001	1A
SWE-M2051.25	SWE-M205DA1.25	1.25A
SWE-M20501.6	SWE-M205DA01.6	1.6A
SWE-M205002	SWE-M205DA002	2A
SWE-M20502.5	SWE-M205DA02.5	2.5A
SWE-M2053.15	SWE-M205DA3.15	3.15A
SWE-M205004	SWE-M205DA004	4A
SWE-M205005	SWE-M205DA005	5A
SWE-M20506.3	SWE-M205DA06.3	6.3A
SWE-M205008	SWE-M205DA008	8A
SWE-M205010	SWE-M205DA010	10A
-	SWE-M205DA12.5	12.5A†
SWE-M205015	SWE-M205DA015	15A†
SWE-M205016	SWE-M205DA016	16A†
-	SWE-M205DA020	20A†



Glass Body



Dimensions in MM

I.R.: 35A or 10x rated current which ever is greater.

Voltage: 250VAC

Pack Size (bag): 5, 10, 100

Holders: Clips (p110)

Blocks (p114)

PCB Mount Holders (p116-117)

Panel Mount Holders (p116, 118)

Inline (p121)

***Approvals Available:** 



Axial leaded versions also available.
See page 148 for further information.

Notes: *The range of M205 products available today is very extensive. We now offer the full range of products from leading brands including Bel Fuse, Bussmann and Littelfuse. All makes offer alternative products in accordance with either European, North American or Asian safety agency approvals. Contact sales with your specific needs and we can offer you the best product to suit your requirements.

† = Non standard rating