

Catalogue No: **P160-F2-3-100-TM**

TBP MCCB 160 FRAME 36kA 30PP 3P 100A ADJ THERM ADJ MAG

Power Distribution and Protection > Circuit Breakers > Moulded Case Circuit Breakers > TemBreak PRO Moulded Case Circuit Breaker > TemBreak PRO 160 AF > 3 Pole



Representative Photo Only
(actual product may vary based on configuration selections)

- General purpose power distribution, motor starting as well as energy metering and communications
- Current limiting device, reduces fault let through energy for increased installation safety
- Direct opening and indication of main contact status – maximising machine and user safety
- Complies to AS / NZS 60947-2, IEC 60947-2 and CE Panel mount standard, with other mounting options
- 1, 2, 3 or 4 pole versions
- Suits XAP chassis, with panelboard options
- Fault ratings: 25, 36, 50, 70, 125 or 200 kA
- Trip unit options include thermal magnetic or electronic types

SPECIFICATIONS

Switching Poles	3P
Utilisation Category	A
Component Type MCCB	MCCB AC
Model	P
Frame Size	160 AF size
Rated Frequency	50 / 60 Hz
Suitable for Distribution Switchboard or MCC	Yes
Trip Unit Rating	100 A
Trip Unit Protection Type	Adjustable Thermal Adjustable Magnetic
In, Rated Current at 30°C	100 A @30°C
In, Rated Current at 35°C	100 A @35°C
In, Rated Current at 40°C	100 A @40°C
In, Rated Current at 45°C	100 A @45°C
In, Rated Current at 50°C	100 A @50°C
In, Rated Current at 55°C	97 A @55°C
In, Rated Current at 60°C	93 A @60°C
In, Rated Current at 65°C	89 A @65°C
In, Rated Current at 70°C	85 A @70°C
Icm, Rated Short-Circuit Making Capacity, 690V AC	6 kA
Ics, Rated Service Short-Circuit Breaking Capacity, 415V AC	36 kA @415VAC
AC Power loss per pole at full rated current	6.7 W
Number of Poles	3
Depth (toggle included)	95.5 mm
Width	90 mm
Weight	1 kg
Electrical Life	30000 cycles
Mechanical Life	50000 cycles
Altitude, Operating (No Derating)	2000 m

Catalogue No: **P160-F2-3-100-TM**

TBP MCCB 160 FRAME 36kA 30PP 3P 100A ADJ THERM ADJ MAG

Power Distribution and Protection > Circuit Breakers > Moulded Case Circuit Breakers > TemBreak PRO Moulded Case Circuit Breaker > TemBreak PRO 160 AF > 3 Pole



Thermal dial setting range Ir (x In)	0.63 - 1
Magnetic Dial setting Im (x In)	6 - 8 - 10 - 12
Cable Cross Section (Min)	1.5 mm ²
Cable Cross Section (Max)	70 mm ²
Terminal Type	Screw Terminal(s)
Pollution Degree	3
DIN rail mounting with optional adapter	Yes
Suitable for Panel Mounting	Yes
Storage Temperature, Min	-10 °C min
Storage Temperature, Max	70 °C max
Operating Temperature, Max	70 °C max
Ir, Thermal Trip Current, Min	63 A
Ir, Thermal Trip Current, Max	100 A
Im, Magnetic Trip Current, Min	600 A
Im, Magnetic Trip Current, Max	1200 A
Vibration Acceleration (Max.)	19 m/s ²
Vibration Frequency, Operational (Max.)	16.7 Hz
Vibration Duration (Max.)	12 min
Certifications	CE DEKRA
Shipping Approvals	Contact NHP

REFERENCES

IECEx Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-