



Quick Overview

Tradesave 150W LED Floodlight

Features

Features & Benefits

- Aluminium housing powder coated black
- Tempered glass lens & polycarbonate cover
- Slim body design
- Constant current driver
- Surge protected 6kV Line-Line, 10kV Line-Earth
- High efficiency SMD chip 125Lm/w
- Operating Temp: -30°C to +50°C
- IP66 rated at IK08 impact resistance

Includes

- Prewired 1.5m 3 core cable

Details

Part No.	TSFL150W
Brand	TRADESAVE
Pack Quantity	1
Unit Of Measure	Each
Voltage AC	200-240V

Proudly Distributed By



☎ 1300 555 586

🌐 www.repelec.com.au

✍ Sign up or log in to repelec.com.au


📘 📷 🐦 📺 @RepelecAU

Page 1

Watt	150
PF	0.95
CCT	5000K
Ra	70
Lifetime (hrs)	63,000
Lumens	18,750
Dimensions (H x W x L) mm	360 x 302 x 67
Beam Angle	120°
Fitting Colour	Black
IK Rating	IK08
Ingress Protection Rating	IP66
Weight (kg)	3.9

Proudly Distributed By



 1300 555 586

 www.repelec.com.au

 Sign up or log in to repelec.com.au

    @RepelecAU

Page 2