

LOW VOLTAGE INDUSTRIAL CABLES

VIPERFLEX H07 RUBBER FLEX CABLES

0.6/1kV VIPERFLEX Control Cables (H07 Rubber & Submersible)

Class 5 Flexible Stranded Bare or Tinned Copper Conductor, Multi Core, EPR Insulated and CPE Sheathed 90°C Submersible (100mtr), Submersion beyond 100mtr is available upon request. Flexible Cords and Cables in Compliance to AS/NZS 5000.1



Type H07 BN-F		Nominal CSA (mm ²)	No. of Cores	Core Lay-up	Cable O.D. (mm)	Approx. Weight (kg/km)
Product Code						
Multi Core > 5G with Earth						
7015ERBC*	7015ERTC	1.5	7G	0+7	11.3	371
1115ERBC*	1115ERTC	1.5	12G	3+9	22.2	606
1118ERBC*	1118ERTC	1.5	18G	6+12	23.5	849
2715ERBC*	2715ERTC	1.5	27G	3+9+15	29.8	1235
7025ERBC*	7025ERTC	2.5	7G	0+7	12.4	566
1225ERBC*	1225ERTC	2.5	12G	3+9	23.9	924
1825ERBC*	1825ERTC*	2.5	18G	6+12	27.9	1295
2725ERBC*	2725ERTC*	2.5	27G	3+9+15	33.4	1884

*Made to order

**Submersible - 100mtr (200mtr and beyond is available on request, subject to minimum order quantities)