

Data sheet | Item number: 773-106

PUSH WIRE® connector for junction boxes; 6-conductor terminal block;
transparent housing; violet cover


www.wago.com/773-106



RoHS 
Compliant

[BOMcheck.net](https://www.bomcheck.net)

Color: 



Data

Electrical data

Ratings per IEC/EN 60664-1

Rated voltage (II / 2)	400 V
Rated impulse voltage (II / 2)	4 kV



Rated current	24 A
Legend (ratings)	(II / 2) $\triangleq$ Overvoltage category II / Pollution degree 2

Connection data

Connection technology	PUSH WIRE®
Actuation type	Push-in
Connectable conductor materials	Copper Aluminum
Solid conductor	0.75 ... 2.5 mm ² / 18 ... 12 AWG
Stranded conductor	1.5 ... 2.5 mm ² / 16 ... 12 AWG
Strip length	12 mm / 0.47 Inch
Total number of connection points	6
Total number of potentials	1
Type of wiring	Side-entry wiring

Geometrical Data

Width	18.8 mm / 0.74 inch
Height	13.1 mm / 0.516 inch
Depth	19.5 mm / 0.768 inch

Material Data

Color	violet
Cover color	violet
Flammability class per UL94	V2
Fire load	0.075 MJ
Weight	3.55 g

Environmental Requirements

Surrounding air (operating) temperature	60 °C
---	-------

Commercial data

GTIN	4044918397681
Product Group	7 (Push Wire Conn.)

Subject to changes.