Product data sheet
Characteristics

WMC310
Clipsal Wilco Rowco - Switched Socket Outlet - 10A - 3 Pin - 1 Pole - 250V

Green Premium™ Product

Main

Range	Clipsal - 56 Series
Product brand	Clipsal
Product or component type	Socket-outlet
Device application	Power supply
Colour	Yellow

Complementary

Number of poles	2
Plug, socket category	Low voltage
Outlet standard	Australian/New Zealand
Plug, socket, control station shape	Straight
Number of modules	2
Number of power socket outlets	1 protective cover
[In] rated current	10 A
[Ue] rated operational voltage	250 V AC 50 Hz
Poles description	1P + N + E
Protection type	Without protection
Device mounting	Surface
Material	Aluminium: cover
Contacts material	Pins: phosphor bronze
Connections - terminals	Screw terminals cable(s) 1.5…16 mm²
Electrical connection	Industrial connector
Depth	116 mm
Width	99 mm
Height	201 mm
Targeted country	Australia

Environment

Standards	AS/NZS 4417.1 AS/NZS 3112
Ambient air temperature for operation	-25…75 °C
IP degree of protection	IP66 conforming to AS 60529

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.82 kg
Package 1 Height	11 cm
Package 1 width	12 cm
Package 1 Length	26 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	4
Package 2 Weight	7.3 kg
Package 2 Height	24.5 cm
Package 2 width	25.3 cm
Package 2 Length	29.8 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Life Is On | CLIPSAL by Schneider Electric